opentext™

OpenText RightFax

Release Notes

10.6 Feature Pack 3 Service Release 7

Product Released: 2018-11-09

Release Notes Revised: 2018-11-09

Contents

| 1 | 1 Introduction | ntroduction4 | | | |
|-----|--|-----------------------------|--|--|--|
| 1.1 | 1.1 Release Notes revision history | 4 | | | |
| 2 | About OpenText RightFax 10.6 Feature Pack 3 Service Release 74 | | | | |
| 3 | 3 New features | 4 | | | |
| 3.1 | | | | | |
| 3.2 | 3.2 Web Client | 4 | | | |
| 3.3 | 3.3 Orphan.exe | 5 | | | |
| | 3.3.1 Using Orphan.exe | 5 | | | |
| 4 | 4 Packaging and documentation | 7 | | | |
| 4.1 | 4.1 Packaging and delivery information | 7 | | | |
| 4.2 | 4.2 Related documentation | 7 | | | |
| 5 | 5 Upgrade notes | 8 | | | |
| 5.1 | 5.1 Preparing to install | 8 | | | |
| | 5.1.1 Preparing to update the RightFax Administr | rative Utilities8 | | | |
| 5.2 | 5.2 Downloading the update | 8 | | | |
| 5.3 | 5.3 Installing the update | <u>e</u> | | | |
| 5.4 | 5.4 Installing the update in a Shared Services system | 10 | | | |
| | 5.4.1 Shut down services and back up the Right | -ax server10 | | | |
| | 5.4.2 Install the update on the first server | 10 | | | |
| | 5.4.3 Repeat on the other servers in the system. | 11 | | | |
| | 5.4.4 Restart RightFax services | 11 | | | |
| 5.5 | 5.5 Installing the update on client computers | 11 | | | |
| | 5.5.1 Updating existing RightFax 10.6 Feature Page 1 | ack 3 client applications11 | | | |
| | 5.5.2 Installing new RightFax 10.6 Feature Pack applications | 3 Service Release 7 client | | | |
| 5.6 | 5.6 Troubleshooting the installation | 12 | | | |
| 6 | 6 Fixed issues | 12 | | | |
| 6.1 | 6.1 Issues fixed in SR7 | 12 | | | |
| 6.2 | 6.2 Issues fixed in SR6 | 21 | | | |
| 6.3 | 6.3 Issues fixed in SR5 | 29 | | | |
| 6.4 | 6.4 Issues fixed in SR4 | 38 | | | |
| 6.5 | 6.5 Issues fixed in SR3 | 44 | | | |
| 6.6 | 6.6 Issues fixed in SR2 | 48 | | | |

| 6.7 | Issues fixed in SR1 | 54 |
|-----|---------------------|----|
| 7 | Contact information | 61 |

1 Introduction

These Release Notes provide an overview of OpenText RightFax 10.6 Feature Pack 3 Service Release 7, including new fixed issues, packaging information, and installation instructions. OpenText recommends that you read these release notes in conjunction with the documentation included with the software package. If any conflicts exist, the release notes supersede the other documentation.

We also recommend that you check OpenText My Support (https://knowledge.opentext.com/) for any service releases or documentation updates that may have been posted after the initial release of OpenText RightFax 10.6 Feature Pack 3 Service Release 7.

1.1 Release Notes revision history

| Revision date | Sections revised | Description of revisions |
|---------------|------------------|--------------------------|
| 2018-02-14 | First release. | All new content. |

2 About OpenText RightFax 10.6 Feature Pack 3 Service Release 7

OpenText RightFax 10.6 Feature Pack 3 Service Release 7 includes new features and bug fixes since the release of OpenText RightFax 10.6 Feature Pack 3 Service Release 6. For details about what is included, see New features and Fixed issues.

OpenText RightFax 10.6 Feature Pack 3 Service Release 7 includes the following new features.

3 New features

3.1 Updated Dialogic Brooktrout SDK

This update includes Dialogic Brooktrout SDK 6.9, which no longer requires installing the Microsoft Visual C++ 2005 Redistributable package on RightFax servers.

3.2 Web Client

- Users can forward or route a fax. Multiple faxes can be selected and forwarded or routed to the same destination.
- Users can select multiple phonebook entries at one time.
- Users can split and combine faxes.
- Users can view and edit the fax information for sent and received faxes.
- Users can print and save faxes without opening the faxes.
- Users can choose the columns to display in the fax list.
- A new column in the fax list displays the Unique ID of each fax.

- Users can search on Unique ID and comments when searching for faxes.
- Users can adjust the font size when annotating faxes.

3.3 Orphan.exe

- New and updated command line options.
- Orphan.exe can be run by the daily maintenance process.

3.3.1 Using Orphan.exe

This following instructions supersede the instructions in the *RightFax Administrator's Guide* and the *RightFax Administrative Utilities Guide* for RightFax 10.6 Feature Pack 3.

About managing orphan image files

Fax image files that do not have any references in the RightFax database are known as orphans. Orphan.exe searches the RightFax server for orphan image files and can perform the following tasks:

- Delete the orphan image files.
- Restore the records of the orphan image files. The files are recovered and associated with a user.
- Create a list of the orphan file images.

Running Orphan.exe in a command line

Orphan.exe is located in the RightFax\Database folder on the RightFax server.

The results are logged in a file named OrphanScan-datetime.log. The log will be saved in the folder where Orphan.exe is located and run. Typically, this is the Database folder. The file lists all of the orphan image files that are found by Orphan.exe and if they were deleted, recovered, or listed.

The Database and RPC services must be running when executing this utility.

| Option | Description |
|-----------------------------|--|
| -i=path | The path to the folder that will be checked for orphan image files. |
| | Example: -i=C:\RIGHTFAX\IMAGE |
| | If the path includes a space character, enclose the string in quotation marks. |
| -S="SqlADOConnectionString" | The SQL ADO connection string that is used to connect to the |
| | RightFax database. Enclose the string in quotation marks. |
| | Example: "Data Source=MYSRV\RightFax;Initial |
| | Catalog=RightFax;Integrated Security=True" |

| Option | Description |
|-----------|--|
| -n | When the command line is run, the program will verify that you wish to proceed. Use this option to skip this prompt. |
| -Z | Delete the orphan image files. |
| -a | Recover the files by associating a user with the orphan image files. The files will appear in the user's fax mailbox. |
| | Specify the user with the user ID (-u) option. |
| -u=UserID | The user ID to whom recovered image files will be associated. This option only is used with the -a option. If you do not specify a user, the files will be associated with the Administrator. The files will appear in this user's fax mailbox. |
| -1 | In text files, create the following files processed by the Orphan.exe program. The following lists will be created: ImageOnlyFiles.txt (for orphan image files that are found in the Image folder) FileList.txt (for orphan image files that are found in the hashed Image folder) The lists will be saved in the folder where Orphan.exe is located and run. Typically, this is the Database folder. The lists will be replaced each time Orphan.exe is run. |
| -d | In the Command Prompt window, list all of the image files processed by the Orphan.exe program. This option is useful for troubleshooting. |
| -g | Orphan.exe evaluates files that were created prior to the past 24 hours, because image files created within the past 24 hours may still be in process and may not be orphans. Use this option to ignore the 24-hour cutoff. Because some image files may not be orphans, this option only should be used for troubleshooting. The list appears in the Command Prompt window. |

Processing orphan image files during the maintenance cycle

Orphan.exe can be run by the daily maintenance process.

The results are logged in the file named MaintOrphanScan.log. The log will be saved in the Database folder.

1. On the RightFax server, open the Windows Registry editor.

- 2. Browse to the fax server key:
 - For 32-bit systems, browse to HKEY_LOCAL_MACHINE\Software\RightFax\Fax\Server.
 - For 64-bit systems, browse to HKEY_LOCAL_MACHINE\Software\Wow6432Node\RightFax\FaxServer.
- 3. Create a REG_DWORD subkey OrphanMode, and specify the value for the action to perform.

| Action | Value |
|---|-------|
| Do not run Orphan.exe. | 0 |
| Create a text file that lists all of the orphaned image files that are processed by the Orphan.exe program. The file lists all of the orphan image files that are found by Orphan.exe and if they were deleted or recovered. The list will be saved in the Database folder. It is named MaintOrphanScan.txt. | 1 |
| Delete orphan image files. | 2 |
| Recover orphan image files. | 3 |

- 4. If orphan image files will be recovered, you can specify the user to receive the orphan image files. The files will appear in the user's fax mailbox. Administrator is the default. To specify a different user, create the REG_SZ subkey OrphanRecoveryUserID.
- 5. Stop and start the RightFax server.

4 Packaging and documentation

Downloads and documentation for OpenText RightFax are available on OpenText My Support (https://support.opentext.com).

4.1 Packaging and delivery information

The software and documentation for OpenText RightFax 10.6 Feature Pack 3 Service Release 7 includes:

- OpenText RightFax 10.6 Feature Pack 3 Service Release 7 installation program
- OpenText RightFax 10.6 Feature Pack 3 Service Release 7 client installation program
- OpenText RightFax 10.6 Feature Pack 3 Service Release 7 Release Notes (this document)

4.2 Related documentation

For additional information about OpenText RightFax or for supplemental information about related products refer to the OpenText RightFax 10.6 Feature Pack 3 documentation, which is available on OpenText My Support (https://knowledge.opentext.com/).

5 Upgrade notes

Before you upgrade, review these instructions.

5.1 Preparing to install

Before you install this update, note the following important information.

- This update is intended for OpenText RightFax 10.6 Feature Pack 3 server and client software. If you have not installed OpenText RightFax 10.6 Feature Pack 3, download it from OpenText My Support and install it before applying this update.
- This update includes an installation program for OpenText RightFax 10.6 Feature Pack 3 Service Release 7 client applications. See <u>Installing new RightFax 10.6 Feature Pack 3 Service Release</u> 7 client applications.
- Apply this update to local RightFax servers before installing it on remote RightFax servers.
- An update to the release notes may be available. Verify that you have obtained the most current release notes from OpenText My Support, https://knowledge.opentext.com/knowledge/llisapi.dll/open/15703289.



Caution

Before applying this update, all remote RightFax services must be shut down. If they are not shut down, data loss can occur. Also, database scripts could be run while a remote server is accessing the database, causing a failure to upgrade the database.



Important

This update includes a new **ConversionControl.xml** file, a new **InsoFieldMap.xml** file, and a new **whitelist.txt** file. The new files will overwrite the existing files. The previous files are backed up in the RightFax\\$Uninstall RightFax 10.6 Feature Pack 3 Service Release 6\ Config folder.

If you customized any of these files, you will need to edit the new files to restore your customizations.

5.1.1 Preparing to update the RightFax Administrative Utilities

To successfully update the RightFax Administrative Utilities, including the RightFax Migration Tool, install the Microsoft Visual C++ 2010 Redistributable Package on the RightFax server before applying the update. The package is available on the Microsoft web site at http://www.microsoft.com/en-us/download/details.aspx?id=5555.

5.2 Downloading the update

Download OpenText RightFax 10.6 Feature Pack 3 Service Release 7 from https://knowledge.opentext.com/knowledge/llisapi.dll/open/15703289.

5.3 Installing the update

To install the update on a RightFax server, complete the following steps:

- 1. Log on to the RightFax server as an Administrator.
- 2. Shut down all RightFax services and applications on the local machine and on all remote servers. Remote servers include:
 - Remote DocTransports.
 - Remote WorkServers.
 - Microsoft Exchange servers that have the RightFax Connector for Exchange installed.
 - Remote Internet Information Servers with RightFax Web applications installed.
- 3. Back up the entire \RightFax directory and the RightFax SQL database.
- 4. Double-click **RightFax10.6FP3SR7.exe**. Files are extracted, and the RightFax 10.6 Feature Pack 3 Service Release 7 installation program opens.
- 5. Click Start.
- 6. If you have backed up the RightFax directories, select the I have backed up my RightFax Installation check box and then click Next.
- 7. The installation program must execute, write, and create SQL statements and requires SQL Server administrator access to the RightFax database. On the RightFax SQL Authentication page, specify the RightFax database to update, the SQL Server administrator user name, and the password for the database. Click **Next**.
- 8. If you have shut down all remote RightFax services or do not use remote RightFax servers, select the **All remote RightFax services have been manually shutdown** check box and then click **Next**.
- 9. The installation program scans the local RightFax server for RightFax services and applications that are running. If RightFax services are running or if you have a RightFax application open, the Applications and Services page appears with a list of services and applications to stop. To allow the installation program to stop applications and services, click **Next**.
- 10. To apply the update, click Next.
- 11. On the Changes Complete page, click **Close** to close the installation wizard.
- 12. Restart RightFax services.
- 13. Repeat these steps on all remote RightFax servers.

5.4 Installing the update in a Shared Services system

If your environment uses the RightFax Shared Services Module, complete the following steps to install the update on each server that is connected with the Shared Services Module.



Important

Installing in a Shared Services system requires down time for all servers joined to the system. Plan your installation accordingly.

To update RightFax servers in a Shared Services system, complete the following general steps:

- 1. Shut down services and back up the RightFax server.
- 2. Install the update on the first server.
- 3. Repeat on the other servers in the system.
- 4. Restart RightFax services.

5.4.1 Shut down services and back up the RightFax server

- 1. Log on to the RightFax server as an administrator.
- 2. Shut down all RightFax services and applications on all RightFax servers that are joined to the Shared Services system and on all remote servers. Remote servers include:
 - Remote DocTransports.
 - Remote WorkServers.
 - Remote E-mail Gateways.
 - Microsoft Exchange servers that have the RightFax Connector for Exchange installed.
 - Remote Internet Information Servers with RightFax Web applications installed.
- 3. Back up the entire $\RightFax\ directory\ and\ the\ RightFax\ SQL\ database.$

5.4.2 Install the update on the first server

- 1. Double-click **RightFax10.6FP3SR7.exe**. The RightFax 10.6 Feature Pack 3 Service Release 7 installation program opens.
- 2. Click Start.
- 3. If you have backed up the RightFax directories, select the I have backed up my RightFax Installation check box and then click Next.
- 4. The installation program must execute, write, and create SQL statements and requires SQL Server Administrator access to the RightFax database. On the RightFax SQL Authentication page, specify the RightFax database to update, the SQL Server administrator user name, and the password for the database. Click **Next**.

- If you have shut down all remote RightFax services or do not use remote RightFax servers, select the All remote RightFax services have been manually shutdown check box and then click Next.
- 6. The installation program will scan the local RightFax server for RightFax services and applications that are running. If RightFax services are running or if you have a RightFax application open, the Applications and Services page appears with a list of services and applications to stop. To allow the installation program to stop applications and services, click **Next**.
- 7. To apply the update, click **Next**.
- 8. On the Changes Complete page, click **Close** to close the installation wizard.
- 9. Restart RightFax services.

5.4.3 Repeat on the other servers in the system

- 1. Repeat the preceding steps on all other servers in the Shared Services system.
- 2. Repeat the preceding steps on all remote RightFax servers.

5.4.4 Restart RightFax services

- 1. Restart each RightFax node, and then restart each remote RightFax server.
- 2. Verify that all servers are back online, and, if necessary, restart RightFax services.

5.5 Installing the update on client computers



Important

Due to changes in RightFax 10.5 groups and cover sheets, you must use RightFax 10.5 or later client applications with RightFax 10.5 or later servers.

5.5.1 Updating existing RightFax 10.6 Feature Pack 3 client applications

To install the update on a client workstation, complete the following steps:

- 1. Log on to the client workstation as an Administrator.
- 2. Double-click **RightFax10.6FP3SR7.exe**. The RightFax 10.6 Feature Pack 3 Service Release 7 installation program opens.
- 3. Click Start.
- 4. If you have backed up the RightFax server installation, select the I have backed up my RightFax installation check box and click Next.
- 5. The installation program will scan the local workstation for RightFax services and applications that are running. If RightFax services are running or if you have a RightFax application open, the Applications and Services page appears with a list of services and applications to stop. To allow the installation program to stop applications and services, click **Next**.
- 6. To apply the update, click **Next**.
- 7. On the Changes Complete page, click **Close** to close the installation wizard.

5.5.2 Installing new RightFax 10.6 Feature Pack 3 Service Release 7 client applications

You can also install fresh RightFax 10.6 Feature Pack 3 Service Release 7 client applications without first installing a previous version. To do so, download the RightFax 10.6 Feature Pack 3 Service Release 7 client installation program from

https://knowledge.opentext.com/knowledge/llisapi.dll/open/15703289 and run **setup.exe**. This installer can also be run from a command prompt. For more information about installing from a command prompt, see the *RightFax Installation Guide*.

5.6 Troubleshooting the installation

The installation program creates a log file that can be referenced for troubleshooting. Look for the file RightFax10_6_FP3SR6_date_time.log in the root of the RightFax program folder.

6 Fixed issues

This section provides information about the issues that have been fixed in this update.

6.1 Issues fixed in SR7

| SR7 | | | |
|----------|-----------------------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-21078 | Administrative Utilities | When running FaxAge.exe and specifying an end date of 12/31/2010, all faxes are marked for deletion. | Fixed. |
| RF-21298 | Administrative Utilities | ImpUser.exe does not link users to Active Directory accounts. | Fixed. |
| RF-21641 | Administrative Utilities | A typographic error appears in an error message in ImpUser.exe. | Fixed. |
| RF-22361 | Administrative Utilities | FaxAge.exe does not authenticate every time it is used. | Fixed. |
| RF-21676 | Conversion Engine | If all pages of a fax attachment are converted as blank pages, the fax will not result in a conversion error. | Fixed. |

| SR7 | | | |
|----------|--------------------------|---|---|
| Issue | Component | Issue description | Resolution |
| RF-22128 | Conversion Engine | Verbose logging reports excessive warnings. | Fixed. |
| RF-21082 | Database | Deleting faxes causes the entry in the Notes table of the database to be deleted. | Fixed. |
| RF-21313 | Database | Database and Server module generate excessive errors and warnings after reconnecting to the database. | Fixed. |
| RF-21554 | Docs-on-Demand Module | Docs-on-Demand Module does not create and send the fax when one-call call type is used. | Fixed. |
| RF-21038 | DocTransport | When appending an IP address to a number, dialing rules strip out the colon in the port address. | Fixed. |
| RF-21203 | DocTransport | When DocTransport is started, the DocTransport OEM service does not start. | Fixed. |
| RF-21356 | DocTransport | ANI blocking does not block faxes from being received. | Fixed. |
| RF-21601 | DocTransport | When a fax takes longer than 1093 minutes to send, the history will show a shorter send period. | Fixed. The history will now show 1092 minutes and 15 seconds. |

| SR7 | | | |
|----------|--------------|--|--|
| Issue | Component | Issue description | Resolution |
| RF-21656 | DocTransport | The customer requested the ability to hide from the history of the faxes the IP address added to a fax number by a dialing rule. | Added. 1. In Windows registry editor, modify HKEY_LOCAL_MACHINE\ Software\RightFax\FaxServer (for X64 systems: HKEY_LOCAL_MACHINE\ Software\Wow6432Node\ RightFax\FaxServer). 2. Create the REG_DWORD value StripIPInFaxNumberHistory. 3. Set the value to 0 to leave the IP address and to 1 to remove the IP address. |
| RF-21962 | DocTransport | Faxes with more than 999 pages submitted to RightFax Connect hang in Scheduled to be Sent status. | Fixed. |
| RF-22081 | DocTransport | Unable to modify the SQL driver for destination tables with an external data source. | Fixed. |
| RF-22324 | DocTransport | Fax channels do not answer inbound calls when the timed ability setting for the DocTransport module switches channels from dial to answer. | Fixed. |
| RF-22537 | DocTransport | Faxes that fail when error correction mode is not enabled can cause .ipk files to be left behind and messages in the message queue. | Fixed. |

| SR7 | | | |
|----------|---------------------------|--|--|
| Issue | Component | Issue description | Resolution |
| RF-22609 | DocTransport | Configuring the automated billing code option with the system default configuration results in an error. | Fixed. |
| RF-22674 | DocTransport | TIFF images are not removed from the DocTransport\Image directory after faxes are sent. | Fixed. |
| RF-22278 | EDC | When a large volume of job files exist, EDC Manager is slow to process items in the Archive directory. | Fixed. |
| RF-20693 | Enterprise Fax Manager | If you exit the user configuration while it is loading the fax numbers as you click on the Routing tab, EFM will crash. | Fixed. |
| RF-20943 | Enterprise Fax Manager | Deleting one of two duplicate numbers in the destination table removes both entries. | Fixed. Duplicates are removed automatically. |
| RF-21184 | Enterprise Fax Manager | When a cover sheet is not sent, the submit date and time on the fax confirmation page displays an incorrect date and time. | Fixed. |
| RF-21185 | Enterprise Fax Manager | EFM profile logs are left behind in the RightFax\Client directory. | Fixed. |
| RF-21295 | Enterprise Fax Manager | When configuring the DEFAULT user, integrated Windows NT security can't be used without selecting a linked account. | Fixed. |
| RF-21305 | Enterprise Fax Manager | When printing the RightFax user list, 10-digit route codes are incorrect. | Fixed. |

| SR7 | | | |
|----------|----------------------------|--|------------|
| Issue | Component | Issue description | Resolution |
| RF-21658 | Enterprise Fax Manager | Connections created by FaxCtrl are not removed from the list of connections when they are closed. | Fixed. |
| RF-21818 | Enterprise Fax Manager | An unenforceable range of channels can be specified when sending via a different DocTransport. | Fixed. |
| RF-21984 | Enterprise Fax Manager | Automatically printed fax confirmations with thumbnails for failed faxes do not show the reason for the failure or the fax transmission history. | Fixed. |
| RF-22327 | Enterprise Fax Manager | Forced scheduling for user groups sets all faxes for the group to delay sending. | Fixed. |
| RF-20778 | Enterprise Fax Reporter | User Inactivity report does not report correct data. | Fixed. |
| RF-21071 | eTransport | When including a cover sheet and choosing to create a PDF, eTransport fails to send. | Fixed. |
| RF-21911 | Exchange Gateway | When sending faxes through Exchange 2016, RightFax does not successfully process all attached message files. | Fixed. |
| RF-22246 | Exchange Web Services | When an email contains email addresses in the CC field, errors are reported by Exchange Web Services. | Fixed. |
| RF-20704 | FaxUtil | If a RightFax group monitor is a delegate of a RightFax user, access is denied when trying to view a fax from the delegator's fax mailbox. | Fixed. |

| SR7 | | | |
|----------------------|-----------|---|---|
| Issue | Component | Issue description | Resolution |
| RF-21052 | FaxUtil | If use trash folder when deleting is enabled, FaxUtil crashes when deleting a fax that is held for preview from the fax viewer. | Fixed. |
| RF-21219 | FaxUtil | Unable to preview the group default coversheet when creating a fax. | Fixed. |
| RF-21327 | FaxUtil | Users can send faxes without filling out the required information. | Fixed. |
| RF-21337 | FaxUtil | FaxUtil uses 8.3 naming convention for attachment names. | Fixed. |
| RF-21405 | FaxUtil | FaxUtil does not open the user and folder that was open at the time FaxUtil was last closed. | Fixed. A new user option is available in FaxUtil on the Other Options tab, Remember folder location between sessions. |
| RF-21704 RF-21074 | FaxUtil | When printing from FaxUtil to a client printer, portions of the page maybe cut off. | Fixed. |
| RF-21868 | FaxUtil | MM/DD/YYYY date format appears on confirmations regardless of the date format that is set on the client or server computer. | Fixed. |
| RF-21913 | FaxUtil | FaxCtrl intermittently changes the communication protocol to TCP/IP when selecting Secure TCP/IP. | Fixed. |
| RF-21949 | FaxUtil | Arabic characters are corrupted on confirmation pages. | Fixed. |

| SR7 | | | |
|----------------------|------------------------|---|-------------------------------------|
| Issue | Component | Issue description | Resolution |
| RF-22137 | FaxUtil | Date disappears from confirmation pages. | Fixed. |
| RF-22298 | FaxUtil | Unable to send combined faxes from FaxUtil. | Fixed. |
| RF-22582 | FaxUtil | The registry key SignaturePositionPercent is not enforced when the signature is being created. | Fixed. |
| RF-22583 | FaxUtil | When a fax is edited, the change isn't recorded in the fax history. | Fixed. |
| RF-22819 | FaxUtil | With FaxUtil in RightFax 16 EP2 or from RightFax 10.6 FP3 with beta releases 5118 and 7107, attempting to print to a client-side printer causes FaxUtil to close. | Fixed. |
| RF-20539 | Installation | When set to a custom location, the Config directory is not updated with the new files included in a RightFax update. | Fixed. |
| RF-21076 | Integration Module | Add support for IBM MQ 9.0. | Added. IBM MQ 9.0 is now supported. |
| RF-20694 | Lotus Notes Gateway | When the Notes user has an apostrophe in their Notes name, the Lotus Notes gateway fails to create user in RightFax. | Fixed. |
| RF-22009 RF-22328 | RightFax Connect | When sent via RightFax Connect, faxes with large attachments fail conversion from IPK to TIFF. | Fixed. |

| SR7 | | | |
|----------------------|--|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-22624 | RightFax Connect Integration Module | When sending through the Integration Module and using RightFax Connect on algorithm 4000, a notification is sent for every attempt. | Fixed. |
| RF-20927 RF-21677 | SAP Gateway | When a user's From Name is defined, certain SAP notifications will fail. | Fixed. |
| RF-20756 | Server | If automatic printing fails, then the Update Status command doesn't work. | Fixed. |
| RF-20781 | Server | The Server module stops processing if a large number of faxes is sent from a phonebook with delay send. | Fixed. |
| RF-20914 | Server | With the RightFax COM API the Delete() method doesn't work with Windows linked credentials. | Fixed. |
| RF-21712 | Server | When opening a fax in Web Client configured for single sign in, RightFax Web Delivery requires manually logging in. | Fixed. |
| RF-22080 | Server | Information in the user's Description field maybe lost when making changes to that user. | Fixed. |
| RF-22086 | Server | Faxes with an English character before a Japanese character cause errors to be created in the RightFax application log. | Fixed. |

| SR7 | | | |
|----------|--------------|--|------------|
| Issue | Component | Issue description | Resolution |
| RF-21097 | SMTP Gateway | Faxes sent from Gmail with the SMTP gateway cause HTML tags to show in body of faxes. | Fixed. |
| RF-22087 | SMTP Gateway | For users set to send faxes with low priority, the faxes that are sent via email change to normal priority during the transmission. | Fixed. |
| RF-22220 | SMTP Gateway | Faxes with digitally signed HTML email bodies are not converting umlaut characters through POP3. | Fixed. |
| RF-22753 | SMTP Gateway | The SMTP gateway does not attempt to retry faxes after a connection error from the SMTP server. | Fixed. |
| RF-20782 | SMTP MFP | The SMTP MFP Connector does not parse FromDIDNum-UserID-ToFaxNumber@domain addressing when the RightFax user ID includes letters and numbers. | Fixed. |
| RF-20699 | Web Client | Search in the Web Client does not use the time on the client computer. | Fixed. |
| RF-21158 | Web Client | When sending from the Web Client and the fax includes an attachment, recipient names with the exclamation point character (!) result in faxes with status of information incomplete. | Fixed. |

| SR7 | | | |
|----------|------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-21769 | Web Client | The Web Client uses the date format of the first browser that connects to it for all users. | Fixed. |
| RF-21869 | Web Client | Users may be able to view faxes for which they don't have permission. | Fixed. |
| RF-22168 | Web Client | Unable to send faxes through the Web Client. | Fixed. |
| RF-20697 | WorkServer | A RightFax WorkServer that is configured solely for the PeopleSoft integration causes the Workserver.exe to consume a large amount of the CPU, up to 50% or more. | Fixed. |
| RF-21458 | WorkServer | When attaching an Office document, then reopening that document before sending the fax, the fax would not generate a conversion error. | Fixed. |
| RF-21514 | WorkServer | CID fonts are not used for PostScript conversions when added to the \RightFax\WorkSrv\GSRes directory. | Fixed. |

6.2 Issues fixed in SR6

| SR6 | | | |
|----------|-----------|--|------------|
| Issue | Component | Issue description | Resolution |
| RF-20203 | COM API | Unable to set a user's voice mail subscriber ID via the COM API. | Fixed. |

| SR6 | SR6 | | | |
|----------|---------------------------|---|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-17718 | Conversion Engine | Hebrew characters in the subject of the message are corrupted during conversion. | Fixed. | |
| RF-19653 | Conversion Engine | Inbound jobs converted to Searchable PDF can become corrupted. | Fixed. | |
| RF-19867 | Conversion Engine | PDF generated by certain bizhub MFPs fail to convert. | Fixed. | |
| RF-20000 | Conversion Engine | Certain text documents are converted with an extra line on the first page. | Fixed. | |
| RF-20859 | Database | When the RightFax server loses connection to a remote SQL database, the database module stops working. | Fixed. | |
| RF-20167 | DocTransport | If a dialing rule references a destination table that does exist, SQL sessions are continuously opened. | Fixed. | |
| RF-20441 | DocTransport | Access or write permission issues can cause outbound RightFax Connect faxes to lose pages. | Fixed. | |
| RF-20470 | DocTransport | Fax status maybe not be updated when sending faxes through RightFax 10.0 Service Release 3 systems. | Fixed. | |
| RF-20513 | DocTransport | Cannot use a custom SIP port. | Fixed. | |
| RF-20290 | Enterprise Fax Manager | When migrating users from one server to another, not all delegates are copied. | Fixed. | |

| SR6 | SR6 | | | |
|----------|-------------------------------|---|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-20703 | Enterprise Fax Manager | When drag and dropping a library document between RightFax servers, the replace all action does not work. | Fixed. | |
| RF-20381 | eTransport | When sending an email from FaxUtil to be processed via eTransport, cannot obtain a complete log. | Fixed. | |
| RF-17207 | Exchange Web Service (EWS) | Event log error should be information only. | Fixed. | |
| RF-20151 | Exchange Web Service (EWS) | Errors are generated when processing fax blasts in a Shared Services system. | Fixed. | |
| RF-19331 | Fax Server | 135,000+ files in the\RightFax\Archive\ directory causes performance degradation. | Fixed. | |
| RF-19796 | Fax Server | If the server maintenance cycle to is set to 11:30 p.m., maintenance events are deleted and a database error occurs when the Server or Database module is opened. | Fixed. | |
| RF-19798 | Fax Server | With NT Authentication and an account is linked to the BuiltIn/BuiltIn account, all faxes submitted via the COM API are sent from the linked account. | Fixed. | |
| RF-19864 | Fax Server | Unable to change or uninstall features in RightFax 10.6 Feature Pack 3 after applying 10.6 Feature Pack 3 Service Release 5. | Fixed. | |

| SR6 | | | |
|----------|-----------------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-20692 | Fax Server | When the SQL server service is stopped, the RightFax Server Module hangs in a "Stopping" state and the RightFax DocTransport and Database Modules remain running. | Fixed. |
| RF-19428 | FaxUtil | In a Citrix XenApp environment, attaching a file in FaxUtil from 'My Documents' generates a file path error. | Fixed. |
| RF-19616 | FaxUtil Fax Server | Delegates with permission to move faxes, but without permission to delete faxes, can move faxes into the trash folder and then empty the trash folder. | Fixed. |
| RF-19664 | FaxUtil | User with delegate permissions to move can delete faxes by moving them into the trash folder when they don't have the delete permission. | Fixed. |
| RF-19716 | FaxUtil | If FaxUtil is pointed to a previous version server, user can't expand groups to see users and their fax folders. | Fixed. |
| RF-19756 | FaxUtil | When closing FaxUtil and the fax viewer is still open, files are left behind in the Temp folder. | Fixed. |
| RF-19792 | FaxUtil | When fax information is edited in FaxUtil, the edits are not retained when routing the fax to a user. | Fixed. |

| SR6 | SR6 | | | |
|----------|-----------|---|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-19811 | FaxUtil | After applying 10.6 FP3 SR5, can't perform searches for faxes in FaxUtil. | Fixed. | |
| RF-19855 | FaxUtil | Shortcut keys for next and previous fax are broken in the viewer. | Fixed. | |
| RF-19865 | FaxUtil | Request to allow the FaxUtil login prompt to allow using NT login credentials. | Fixed. | |
| RF-19970 | FaxUtil | Search criteria that contains more than one special character does not work. | Fixed. | |
| RF-20030 | FaxUtil | Cannot search for statuses in FaxUtil. | Fixed. | |
| RF-20046 | FaxUtil | Data added via "Edit fax information" cannot be deleted. | Fixed. | |
| RF-20054 | FaxUtil | When loading additional phonebooks, not all personal phonebook entries are displayed. | Fixed. | |
| RF-20056 | FaxUtil | The settings for priority delta in dialing rules does not show accurate information. | Fixed. | |
| RF-20294 | FaxUtil | The filter option is not available when forwarding a fax to a user. | Fixed. | |

| SR6 | | | |
|----------|---------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-20396 | FaxUtil | Saving a large TIFF file from the viewer to a location with Distributed File System replication enabled fails with the error "An error occurred when saving the fax: The process cannot access the file because it is being used by another process." | Fixed. |
| RF-20484 | FaxUtil | When routing a fax to more than two users, the history does not show all users. | Fixed. |
| RF-20538 | FaxUtil | When a delegate forwards a fax to another user via email, then the fax doesn't include the forward event or notes added by the delegate. | Fixed. |
| RF-20299 | Notes Gateway | Using a forward slash in the To Name of the notes address corrupts the To Name. | Fixed. |
| RF-18292 | Ricoh MFP | The Ricoh client application sends post commands when the client is not being used. | Fixed. |
| RF-18452 | Ricoh MFP | A memory leak occurs when using the Ricoh connector with over 9000 devices. | Fixed. |
| RF-18862 | Ricoh MFP | Faxes sent from Ricoh MFP sends a 169.*.*.* APIPA address. | Fixed. |
| RF-19342 | Ricoh MFP | Unable to scan and fax from Ricoh Aficio SP5200. | Fixed. |

| SR6 | SR6 | | | |
|----------|--------------------------|--|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-20405 | Ricoh MFP | Build-up of empty folders in C:\Program Files (x86)\RightFax\EDC\Modules\ Ricoh\DIB\FileStore. | Fixed. | |
| RF-19774 | RightFax Connect | When RightFax Connect is configured to send as PDF, DocTransport will discard the fax. | Fixed. | |
| RF-19802 | RightFax Connect | RightFax Connect faxes that fail on the first attempt and succeed on a later attempt, both abandoned and successful sent notifications are sent. | Fixed. | |
| RF-19264 | SMTP Gateway | Cannot add more than 10 email gateways. | Fixed. | |
| RF-20131 | SMTP Gateway | User authentication is required when the SMTP gateway is configured to not require authentication. | Fixed. | |
| RF-20301 | SMTP Gateway | Hebrew characters in the From field of the SMTP gateway configuration are corrupted. | Fixed. | |
| RF-19684 | Sync Module | If a group of users is removed from Active Directory, the Sync Module stops. | Fixed. | |
| RF-19394 | Vault / XML Generator | Some XML files contain duplicate data when additional FileCopy and GenText services are used with RightFax Vault or XML Generator. | Fixed. | |

| SR6 | SR6 | | | |
|----------|--------------------------------|---|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-20053 | Web API | When using a multi-threaded application to save faxes as PDF via the Web API, invalid PDF files are created. | Fixed. | |
| RF-19801 | Web Client | In the role of a delegate, the user cannot view a fax that is found in a search without using the delegate's folder. | Fixed. | |
| RF-19890 | Web Client | When attempting to perform a search on the comment field, no data is returned unless it is an exact match. | Fixed. | |
| RF-19953 | Web Client | Automatic OCR setting in Web Client overrides the user permission to disable it in EFM. | Fixed. | |
| RF-20442 | Web Client | User cannot select a cover sheet in Web Client when the Group setting "All faxes must have cover sheets" is selected. | Fixed. | |
| RF-20508 | Web Client | Web Client search filters for Start Time and End Time do not function. | Fixed. | |
| RF-20645 | Web Client | When searching for a user by name in the Web Client, the search fails. | Fixed. | |
| RF-20682 | Web Client | In the role of Reviewer delegate, the user cannot view a fax that is found in a search. | Fixed. | |
| RF-19595 | Web Server Status Dashboard | Dashboard displays incorrect DocTransport status. | Fixed. | |

| SR6 | | | |
|----------|--------------------------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-19945 | Web Server Status Dashboard | The Dashboard system overview is blank. When attempting to edit servers in the Edit server list, an error occurs. The Edit Server List link is missing unless the browser is run as | Fixed. |
| RF-19648 | WorkServer | Administrator. FaxStatus not showing the values of the service which the WorkServer is configured to | Fixed. |
| | | process. | |
| RF-20826 | WorkServer | When submitting a specific PDF, all body pages are identified as blank and are discarded. | Fixed. |

6.3 Issues fixed in SR5

| SR5 | | | |
|----------|-------------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-18265 | COM API | The COM API does not include all user permissions. | Fixed. |
| RF-19227 | Conversion Engine | When INSO is used for HTML conversion, the document margins are not correct. | Fixed. |
| RF-19112 | Conversion Engine | If a coversheet fails to convert and the fax is kicked, the incorrect coversheet is used. | Fixed. |

| SR5 | | | | |
|----------|-------------------|--|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-18815 | Conversion Engine | When attempting to send a large bitmap, the fax hangs in the conversion process indefinitely, and copies of the fax image are continually created. | Fixed. | |
| RF-19596 | DocTransport | Incorrect status from RightFax Connect and FaxUtil on special info or number no longer in service tone. | Fixed. | |
| RF-19587 | DocTransport | RightFax Connect outbound faxes fail with a transmission error about converting IPK to TIF. | Fixed. | |
| RF-19586 | DocTransport | Mixed conversion quality between cover and body can cause faxes to fail and the error "No Answer at Fax Number." | Fixed. | |
| RF-19445 | DocTransport | When a receiving fax service disconnects, the DocTransport service does not terminate the connection and logs an unknown error. | Fixed. | |
| RF-19212 | DocTransport | Dialing rules with destination tables from an external data source do not function. | Fixed. | |
| RF-19122 | DocTransport | When the Mobility Push Proxy Gateway is added as a transport method, DocTransport crashes on startup. | Fixed. | |

| SR5 | | | |
|----------|----------------------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-18566 | DocTransport | When a dialing rule is named with the character "N," the rule does not work. | Fixed. |
| RF-16990 | DocTransport | If a dialing rule is set to delay faxes by a specific interval of time, the faxes cannot be manually released in FaxUtil. | Fixed. |
| RF-18384 | Documentation | RightFax Printer Driver is not created by the client installation program. | Fixed. |
| RF-18803 | Enterprise Fax Manager | When a duplicate user is created in EFM, a descriptive error is not displayed. | Fixed. |
| RF-18156 | Enterprise Fax Reporter | The report Automation_Outbound_Day.rpt incorrectly reports zero pages sent for faxes with multiple retries that sent correctly. | Fixed. |
| RF-17769 | Exchange Connector | When using the Exchange Connector as the inbound routing method, Hebrew characters do not display correctly in the transmission history. | Fixed. |
| RF-17734 | Exchange Gateway | When Cover Sheet Resolution is set for Fine Mode, cover sheets sent from Outlook with manual addressing are converted in Normal Mode. | Fixed. |

| SR5 | | | |
|----------|-----------------------------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-17889 | Exchange Web Service (EWS) | When using EWS to send received fax notifications, Hebrew characters in the user ID will be replaced with garbage characters in the subject line. | Fixed. |
| RF-19542 | External Document Connector | When a user ID contains numerals, the SMTP Connector for MFP does not correctly parse FromUserID-ToFaxNumber@Domain. | Fixed. |
| RF-18808 | External Document Connector | Printed confirmation page from Xerox MFP is incomplete. | Fixed. |
| RF-18671 | External Document Connector | With the RightFax Konica Minolta bEST Connector, users cannot authenticate with single sign-on from Equitrac. | Fixed. |
| RF-18163 | External Document Connector | If SMTP MFP in EDC is configured with two RFSendStatus services, thumbnail images do not appear on print notifications. | Fixed. |
| RF-17725 | External Document Connector | A GenImage Service cannot be added to a remote EDC server. | Fixed. |
| RF-17697 | External Document Connector | In a system with more than one GenImage Service, fax jobs are delayed. | Fixed. |
| RF-16724 | External Document Connector | When more than one GenImage Service is running, it locks up and becomes unresponsive. | Fixed. |

| SR5 | | | |
|----------|------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-18714 | Fax Server | In high volume environments, Orphan.exe runs for several hours. | Fixed. |
| RF-18538 | Fax Server | When the server is under load, the statuses of RightFax Connect jobs are incorrect in FaxUtil. | Fixed. |
| RF-17644 | Fax Server | When sending via POP3, the user's setting for cover sheet resolution is not used. | Fixed. |
| RF-16609 | Fax Server | When the server module is unable to locate the EVERYONE group administrator account, faxes fail to send and an unhelpful error message reported. | Fixed. |
| RF-19923 | FaxUtil | FaxUtil performance is extremely slow when connected via a VPN. | Fixed. |
| RF-19490 | FaxUtil | In the RightFax Viewer, the delegate permission "Can edit faxes" does not allow delegates to edit faxes. | Fixed. |
| RF-19442 | FaxUtil | When annotating multiple pages and printing without closing and opening the fax or returning to the first page before printing, annotations on the first page of a multi-page fax do not print. | Fixed. |

| SR5 | | | | |
|----------|-----------|---|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-19395 | FaxUtil | When printing multiple faxes to a printer that is not the default printer on the client workstation, the faxes are not sent to the correct printer. | Fixed. | |
| RF-19285 | FaxUtil | Move to Folder moves a fax to the Main folder if OK is clicked in the Move Folder dialog box and a folder is not selected. | Fixed. | |
| RF-19248 | FaxUtil | If a user account is not configured with a password or the password is incorrect, then other users cannot load the user's phonebook and an error message doesn't display. | Fixed. | |
| RF-19204 | FaxUtil | When upgrading FaxUtil from version10.6 FP3 SR3 to 10.6 FP3 SR4, the installation fails and the error "A newer version of RightFax is installed" is reported. | Fixed. | |
| RF-19151 | FaxUtil | When a fax is successfully sent but fails to automatically print, the Confirmation button and "Show Confirmation page" option are not available. | Fixed. | |
| RF-18851 | FaxUtil | When using an account that has a space in the Windows user name, faxes cannot be viewed in the RightFax Viewer. | Fixed. | |
| RF-18713 | FaxUtil | In FaxUtil if the setting "Show n faxes" is changed, and the application is restarted, then the setting is ignored. | Fixed. | |

| SR5 | | | | |
|----------|-------------------------|---|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-18637 | FaxUtil | In the RightFax Viewer, the CTRL+R keyboard shortcut does not open the FaxUtil Route Fax dialog box. | Fixed. | |
| RF-18636 | FaxUtil | In the RightFax Viewer, the Delete key on the keyboard and the CTRL +D keyboard shortcut do not open the FaxUtil delete fax dialog box. | Fixed. | |
| RF-19920 | Lotus Notes Gateway | When the Lotus Notes gateway receives a fax with over 137 characters in the TO NAME field, the gateway crashes. | Fixed. | |
| RF-18858 | Lotus Notes Gateway | When a fax is received via the Lotus Notes Email Gateway Module, the subject line of the email is not included on the notification message. | Fixed. | |
| RF-16639 | Outlook Advanced Fax | Outlook Advanced Fax form "Save as Default" option does not save alternate Cover Sheet preference. | Fixed. | |
| RF-19281 | SMTP Gateway | When attempting to send a fax to multiple addresses using a semicolon as a delimiter, the fax only is sent to the last email address in the string. | Fixed. | |
| RF-19145 | SMTP Gateway | When inbound faxes are routed to email via the SMTP gateway, the body of the transmission history appears twice in the body of the email. | Fixed. | |

| SR5 | | | |
|----------|--------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-18840 | SMTP Gateway | If an email address does not exist on a mail server and RightFax tries to send an inbound notification to the address, the gateway will retry to send the message indefinitely. | Fixed. |
| RF-18605 | SMTP Gateway | Embedded codes in email are not processed by the SMTP gateway. | Fixed. |
| RF-18437 | SMTP Gateway | When the subject has nine or more characters and diacritical characters and ~7 is enabled in custom messages, spaces are replaced with underscores in the email notification. | Fixed. |
| RF-17929 | SMTP Gateway | When attempting to send a notification to multiple addresses using a semicolon as a delimiter, an error occurs and the notification is not sent. | Fixed. |

| SR5 | SR5 | | | |
|----------|--------------|--|---|--|
| Issue | Component | Issue description | Resolution | |
| RF-16904 | SMTP Gateway | When using the {FxHandle} macro in the WebDeliveryURLOverride registry key, the handle in the URL of the notification is from the dbo.DocFile table in the RightFax database, not from the dbo.Documents table. This links to the fax list instead of the fax. | The correct format of the WebDeliveryURLOverride registry key is: http://{WebServer}/WebClient/ WebClient.dll/?X=LNKFX&SE RVER={RFServer}&HFAX={F xHandle} {WebServer} Name of the IIS server hosting the web application {RFServer} Name of the RightFaxserver {FxHandle} Handle of the fax The user documentation has been updated. | |
| RF-19553 | Web Client | When multiple users are logged in to the Web Client and are moving between folders simultaneously, users are unable to open folders. | Fixed. | |
| RF-19489 | Web Client | Administrator cannot disable auto-forwarding of faxes. | Fixed. | |
| RF-19403 | Web Client | When a fax is opened in Web Client, PDF and GIF files are created in the folder \RightFax\WebApps\WebClient \Cache, and the files are not deleted. | Fixed. | |
| RF-18959 | Web Client | When more than 10 billing codes appear in a search, and the user chooses the 11 th or later billing code, then the incorrect billing code is used. | Fixed. | |

| SR5 | | | |
|----------|------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-17960 | Web Client | Delegates with Editor permission in the Web Client cannot rename folders. | Fixed. |

6.4 Issues fixed in SR4

| SR4 | SR4 | | | |
|----------|-------------------|--|---|--|
| Issue | Component | Issue description | Resolution | |
| RF-18076 | Conversion Engine | OpenDocument Format (ODF) files fail to convert. | Fixed. | |
| RF-17704 | DocTransport | Doctransport.exe crashes when using T.37 FOIP transport type. | Fixed. | |
| RF-17919 | DocTransport | The user documentation does not list the macros for the Calling Party field. | Fixed. ~1 Fax number dialed. ~2 RightFax user ID of sender. ~3 Recipient's voice number. ~4 Recipient's name. ~5 Recipient's company name. ~6 Billing code 1. ~7 Billing code 2. ~8 Assigned unique ID for fax job. ~9 CSID match code for secure send operation. ~0 Name of the sender. ~A Source server IP address or name. ~B User's fax number. | |
| RF-18112 | DocTransport | Faxes received via RFConnect do not open. | Fixed. | |

| SR4 | SR4 | | | |
|----------|-----------------------------------|--|---|--|
| Issue | Component | Issue description | Resolution | |
| RF-18114 | DocTransport | Faxes are sent successfully despite having more pages than defined in "Max. Pages Channel may Send." | Fixed. | |
| RF-18552 | DocTransport | A dialing rule referencing a non-existent destination table causes SQL sessions to open each time the rule is evaluated. | Fixed. | |
| RF-16599 | Enterprise Fax Manager | List of users does not sort by route code if codes are 10 digits or longer. | Fixed. | |
| RF-17951 | Enterprise Fax Manager | Red indicator on RightFax Server is confusing: All services are running, but the indicator is RED because the disk space is 8% or below. | Fixed. Red indicator no longer used to indicate low disk space. It is only used to indicate that one or more services are not running. | |
| RF-18272 | Enterprise Fax Manager | EFM crashes when attempting to add fax numbers that already exist. | Fixed. | |
| RF-18383 | Enterprise Fax Manager | .CMD files in CMDDATA folder are not being cleared out during maintenance. | Fixed. | |
| RF-17980 | Exchange Email Gateway | "Include fax with notifications" settings are not honored when sending fax from Outlook. | Fixed. | |
| RF-16723 | External Document Connector | After several successful logins with a user's NT log in, Ricoh MFP defaults to the Walkup user account. | Fixed. | |

| SR4 | SR4 | | | |
|----------|-----------------------------------|---|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-17727 | External Document Connector | The GenImage process notifications for HP jobs processed through EDC is exceedingly slow. | Fixed. | |
| RF-17807 | External Document Connector | Unable to set the default domain in EDC for the Konica Minolta bEST Connector. | Fixed. | |
| RF-17870 | External Document Connector | Unable to send fax to email address from a Konica Minolta MFP. | Fixed. | |
| RF-17946 | External Document Connector | XeroxEIP module enters into an endless loop when it does not receive a job status update. Fail-safe does not exist. | Fixed. | |
| RF-17958 | External Document Connector | Administrator can add more SMTP-capable devices than are licensed. | Fixed. | |
| RF-18123 | External Document Connector | Ricoh MFPs leave behind empty folders in \Ricoh\DIB\Filestore. | Fixed. | |
| RF-18602 | External Document Connector | Single sign-on not functioning for Konica Minolta Native connector. The User must enter sign-on credentials instead of being signed on automatically. | Fixed. | |
| RF-16812 | FaxUtil | No results returned when searching received faxes by From Name value. | Fixed. | |
| RF-17133 | FaxUtil | When printing a faxed PDF, the bottom edge of the fax image is cut-off. | Fixed. | |

| SR4 | SR4 | | | |
|----------|--------------------------|--|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-17787 | FaxUtil | FaxUtil fails to import phonebook entries that include blank fields. | Fixed. | |
| RF-17819 | FaxUtil | When users attempt to edit fax information, the Window of the open fax is moved behind the FaxUtil window. | Fixed. | |
| RF-18175 | FaxUtil | Delegates that lack the "Save As" and "Send via E-mail" permissions can perform these actions. | Fixed. | |
| RF-18308 | FaxUtil | Zoom settings for a fax are not being retained. | Fixed. | |
| RF-18525 | FaxUtil | Faxes sent between 11:00PM and 12:00AM are placed into the queue of the next day. | Fixed. | |
| RF-18599 | Installation | RightFax not installing if a newer version of Microsoft Visual C++ is installed on the server. | Fixed. | |
| RF-17895 | Integration Module | When converted to fax, a PDF attachment contains a false first page with FCL code. | Fixed. | |
| RF-17631 | Lotus Notes gateway | No email notification is sent when a fax fails to send from IBM Notes. | Fixed. | |
| RF-17850 | Outlook Advanced Form | Unable to export or move emails to another folder when the Outlook Advanced add-in is enabled. | Fixed. | |

| SR4 | | | |
|----------|---------------|--|------------|
| Issue | Component | Issue description | Resolution |
| RF-17751 | RFConnect | If a fax fails all transmission attempts, the email notification incorrectly states that the fax failed after just one attempt. | Fixed. |
| RF-17956 | Server module | User IDs of 21 Characters are truncated to 20 when created with COMAPI. | Fixed. |
| RF-18117 | Server module | The "DeleteImagesOnPurge" FaxServer registry key does not remove the annotated images. | Fixed. |
| RF-18378 | Server module | The "DeleteImagesOnPurge" FaxServer registry key does not immediately delete the fax image of a received fax that was forwarded. | Fixed. |
| RF-18459 | SMTP Gateway | Image files, such as .jpg and .gif files attached to a Rich Text format email are stripped during the conversion to fax. | Fixed. |
| RF-17925 | Web Client | Only 20 users available in Delegates list. | Fixed. |
| RF-17992 | Web Client | Delegate cannot log into the mailbox of the delegator if the delegator's user ID starts with #. | Fixed. |
| RF-18121 | Web Client | Unable to sign on to Web Client when LTPA technology is used. | Fixed. |

| SR4 | SR4 | | | |
|----------|------------|--|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-18217 | Web Client | Members of a group with the restriction "All faxes must have cover sheets" can delete coversheets and deselect "Use cover sheet." | Fixed. | |
| RF-18266 | Web Client | Unable to log into Web Client when the LTPA token contains too many characters. | Fixed. | |
| RF-18442 | Web Client | The error "The Web Client is unable to allocate any more memory" is generated after viewing the Fax History | Fixed. | |
| RF-18454 | Web Client | The error "The Web Client is unable to allocate any more memory" is generated after cancelling an action, such as forwarding or routing a fax. | Fixed. | |
| RF-18582 | Web Client | Annotations not updated after fax has been saved as PDF or TIFF. | Fixed. | |
| RF-17602 | WorkServer | WorkServer no longer uses the CID fonts placed into the \RightFax\WorkSrv\GSRes folder to create and convert documents. | Fixed. | |
| RF-17630 | WorkServer | When performing a server print, an error is generated such as: Error finding C:\Windows\TEMP\WORKS RV3\WORKSRV. | Fixed. | |
| RF-18115 | WorkServer | Jobs sent from the GetPaid app to a fax number fail to convert. | Fixed. | |

6.5 Issues fixed in SR3

| SR3 | SR3 | | | |
|----------|-----------------------------|--|---|--|
| Issue | Component | Issue description | Resolution | |
| RF-16896 | Administrative Utilities | Missing user permissions in Impuser.exe | Fixed. | |
| RF-16974 | COM API | Unable to set the IsGeneric2On flag to True via COM API. | Fixed. | |
| RF-16440 | Conversion Engine | When comma (,) is used as a decimal indicator, HTML documents are identified as blank pages and removed. | Fixed. | |
| RF-16957 | Conversion Engine | Apache Office Writer documents file types fail conversion. | Fixed. | |
| RF-17061 | Conversion Engine | When submitting a fax with embedded codes to HPFAX, diacritical characters are not converted correctly. | In Worksrv configuration, clear the check box "Use PCL converter for text files." | |
| RF-17291 | Database module | SQL deadlocks to WORKREQUEST Table. | Fixed. | |
| RF-16520 | DocTransport | Asterisk (*) is stripped when dialing. | Fixed. | |
| RF-17673 | DocTransport | When using RightFax Connect, if an error occurs during the release, inbound faxes are lost and outbound faxes do not update. | Fixed. | |
| RF-18112 | DocTransport | Unable to view faxes received via RightFax Connect. | Fixed. | |

| SR3 | | | |
|----------|--------------------------------------|---|--|
| Issue | Component | Issue description | Resolution |
| RF-16856 | Enterprise Fax Manager | Contents in Help menu does not work. | Fixed. Removed the Help/Contents menu. This Help system is no longer provided for EFM. |
| RF-17818 | Enterprise Fax Manager | Unable to point a Destination Table at a SQL Database due to "Error 1615 working with the fax server. SQL query syntax invalid or unsupported." | Fixed. |
| RF-17503 | EWS Connector for Microsoft Exchange | FAX address does not work in EWS. | Fixed. |
| RF-17519 | Exchange Connector | Mail Merge jobs submitted through Exchange Connector fail to convert. | Fixed. |
| RF-17052 | Exchange Email Gateway | Invalid characters in email notifications when using French characters in Custom Messages. | Fixed. |
| RF-17173 | Exchange Email Gateway | Plain text faxes with blank body and encoded in UTF-8 fail with the error "Problem Converting Fax Body or Cover Sheet" | Fixed. |
| RF-16482 | External Document Connector | HP MFP Print confirmation does not include all details. | Fixed. |
| RF-17046 | External Document Connector | When stopping or starting EDC Manager Module via EFM, not all EDC services are affected. | Fixed. |
| RF-18122 | External Document Connector | Ricoh DIB only allows a single device to connect. | Fixed. |

| SR3 | SR3 | | | |
|----------|--|--|---|--|
| Issue | Component | Issue description | Resolution | |
| RF-16988 | External Document Connector for Ricoh | 12.x Ricoh connector post frequency causes IIS logging to use a large amount of disk space and network activity. | Uninstall the old connector from devices and install the new RightFax client for SDK_J. | |
| RF-17026 | External Document Connector for Ricoh | If the application pool that is running the Ricoh DIB site is recycled during use the job never gets sent out. | Uninstall the old connector from devices and install the new RightFax Client for SDK_J. | |
| RF-17064 | FaxUtil | Reset button does not clear Start Date and Time and End Date and Time fields. | Fixed. | |
| RF-17268 | FaxUtil | FaxUtil does not sort by To/From/File and FaxNumber/Email/ID. | Fixed. | |
| RF-17379 | FaxUtil | Not all faxes are cancelled if deleted while sending. | Fixed. | |
| RF-11434 | Remoting Service | Remoting module memory leak when using Ricoh DIB with 30+ devices. | Fixed. | |
| RF-13808 | RightFax Connect | RightFax Connect continues to attempt to send faxes when it is unable to connect to the Cloud server. | Fixed. | |
| RF-16982 | RightFax Connect | When using RightFax Connect and Retry Algorithm 4000 and Attempt Level Reporting, notifications are not sent for each failure, but are all sent after the last failure. | Fixed. | |
| RF-17674 | RightFax Connect | RightFax does not adhere to configured server module retries when using RightFax Connect on algorithm 58. | Fixed. | |

| SR3 | SR3 | | | |
|----------|--------------------------------|---|------------|--|
| Issue | Component | Issue description | Resolution | |
| RF-17691 | RightFax Connect | Fax history does not record the pages sent on a failed outbound fax when using RightFax Connect. | Fixed. | |
| RF-17594 | RightFax Connect. DocTransport | Support TLS 1.2 for RightFax Connect. | Fixed. | |
| RF-17536 | RightFax Server | User permission Assign Default Billing Codes to Received Faxes not functioning. | Fixed. | |
| RF-16735 | SMTP Gateway | The registry key "GatewayEnforceRequiredCov ersheetFields" sends duplicate notifications for incomplete faxes. | Fixed. | |
| RF-16916 | Web Client | Web Client login will fail with passwords over 19 characters. | Fixed. | |
| RF-17470 | Web Client | In Web Client, Client Date / Time set to client time displays GMT. | Fixed. | |
| RF-17482 | Web Client | In Web Client, Fax History set to client time displays server time. | Fixed. | |
| RF-17761 | Web Client | Web Client does not show date with time for faxes over a week old. | Fixed. | |
| RF-17804 | Web Client | When NT linked delegate users attempt to open a fax using links sent through Web Delivery, the fax does not open in Web Client. | Fixed. | |

| SR3 | | | |
|----------|------------|---|------------|
| Issue | Component | Issue description | Resolution |
| RF-17071 | WorkServer | Thumbnail is not included on the auto-print page for failed outbound faxes. | Fixed. |

6.6 Issues fixed in SR2

| SR2 | SR2 | | | |
|----------------------------------|-----------------------------|---|------------|--|
| Issue | Component | Issue Description | Resolution | |
| RF-16300 | Administrative Utilities | Cannot upgrade to the latest release using the RightFax Database Upgrader Tool. | Fixed. | |
| RF-16019 | Conversion Engine | Certain conversions fail with the error <i>Word has</i> encountered a problem due to Word memory usage not resetting. | Fixed. | |
| RF-16329 RF-16333 | Conversion Engine | Poor conversion quality of emails that have plain text bodies and no attachments. | Fixed. | |
| RF-16334 RF-16335 RF-16985 | Conversion Engine | Emails submitted with text- only attachments may result in faxes containing the attachment content in the fax body. | Fixed. | |
| RF-16412 | Conversion Engine | JPG files fail conversion or convert with unacceptable quality. | Fixed. | |
| RF-16581 | Database RFConnect | The JobID is removed from a fax submitted to RFConnect while its status is Scheduled to be Sent. | Fixed. | |

| SR2 | | | |
|----------|---------------------------|---|------------|
| Issue | Component | Issue Description | Resolution |
| RF-16014 | DocTransport | Least-cost dialing rules cause faxes to get stuck in Sending status. | Fixed. |
| RF-16096 | DocTransport | Least-cost dialing rules and call grouping cause faxes to get stuck in <i>Scheduled to be sent</i> and <i>Sending</i> statuses. | Fixed. |
| RF-16230 | DocTransport RFConnect | Smart Resume with an RFConnect DocTransport results in a fax scheduling error on the second attempt to send the fax. | Fixed. |
| RF-16233 | DocTransport | When sending faxes using a DocTransport configured for call grouping, if one fax in a group fails with a transmission failure and all subsequent fax send successfully, all faxes in the group are sent again every time the DocTransport is restarted. | Fixed. |
| RF-16242 | DocTransport | Faxes attempting to use Post Dialing fail with a status Phone Line Problem. | Fixed. |
| RF-16255 | DocTransport | Stopping DocTransport while the lines are in use can cause faxes to get stuck in Scheduled to be sent. | Fixed. |
| RF-16477 | DocTransport | Faxes routed into the local server using the * dialing rule are resent when the DocTransport is restarted. | Fixed. |

| SR2 | SR2 | | | |
|----------|----------------------------|---|------------|--|
| Issue | Component | Issue Description | Resolution | |
| RF-16728 | DocTransport | Sending a fax with 999 pages in FaxUtil results in a status of Fax Blocked from Dialing Phone Number. | Fixed. | |
| RF-17070 | DocTransport | When a fax is deleted and DocTransport removes the call from the channel, subsequent faxes that use the channel are given an OK status but no pages send. | Fixed. | |
| RF-16142 | Enterprise Fax Manager | When copying users using the Append Phonebooks Only setting, phonebook entries are not appended if any entry on the source server exists on the destination server. | Fixed. | |
| RF-16252 | Enterprise Fax Manager | The Printer list for the user's inbound Automatic Printing Options is not sorted alphabetically. | Fixed. | |
| RF-15995 | Enterprise Fax Reporter | Some reports (AdvancedAuditReport, Delegates_User, and Permissions_by_User) fail authentication while others do not. | Fixed. | |
| RF-16796 | Enterprise Fax Reporter | EnterpriseFaxReporter.exe command line not responding | Fixed. | |
| RF-16022 | FaxUtil | If the TO Name of a fax includes a single quotation mark, the fax fails to open. | Fixed. | |
| RF-16696 | FaxUtil | The phonebook filter options are missing. | Fixed. | |

| SR2 | | | |
|----------|--------------------|---|------------|
| Issue | Component | Issue Description | Resolution |
| RF-15342 | Integration Module | Attached document submitted with false first page via Integration module displays FCL code within the image. | Fixed. |
| RF-16005 | Integration Module | Shutting down the Integration module is delayed by MQGet processes. | Fixed. |
| RF-16453 | Integration Module | The {{NOCOVER}} FCL code is ignored when faxes are submitted via the Integration Module inbox folder. | Fixed. |
| RF-16498 | Java/XML API | Sending and querying a fax using the Java/XML API returns a value of 1970 instead of the correct SEND_DATETIME. | Fixed. |

| SR2 | | | |
|----------|-----------------------|---|---|
| Issue | Component | Issue Description | Resolution |
| RF-10856 | Server module FaxUtil | FaxUtil and Web Client users are not prevented from autoforwarding faxes to themselves, numbers outside of RightFax, and unknown fax numbers. | A client-side registry key has been added with which you can disable the automatic forwarding options on the Receiving tab in FaxUtil and Web Client. To restrict automatic forwarding, follow these steps on the client machine: |
| | | | Shut down FaxUtil or Web Client if it is running. |
| | | | 2. Open the registry editor to the key HKEY_CURRENT_USER \Software\RightFax Client\FUW32\ (x64: HKEY_LOCAL_MACHIN E\ Software\Wow6432Node\ RightFax Client\FUW32\). |
| | | | Create a new DWORD called LockAutoForwardConfig . |
| | | | 4. To disable the Automatic Forwarding options on the client, set the value to 1. When set to the default value 0, Automatic Forwarding can be configured. |
| RF-15999 | Server module | If for any reason the Server module cannot write to a .3xx file, the RTI line will not be stamped on subsequent pages. | Fixed. |

| SR2 | SR2 | | | |
|----------|--------------|--|---|--|
| Issue | Component | Issue Description | Resolution | |
| RF-16455 | SMTP Gateway | A RightFax user configured to receive notifications of incomplete faxes is not notified when an incomplete fax is sent via the SMTP gateway. | To resolve this issue: 1. Open the Registry Editor to HKEY_LOCAL_MACHIN E\Software\Wow6432Nod e\RightFax\FaxServer. 2. Set the following DWORD registry keys: to a value of 1: NotifyViaFrom_nameFallbac k GatewayEnforceRequiredCo versheetFields If you are having the faxes sent through the Default user, keep the Notification Address/Info box on the Notification tab of the Default | |
| RF-16457 | Vault | When the Vault source folder exceeds 65535 files, EDC stops processing and Faxserv.exe performance degrades. | user account blank to send back to the originating user. Fixed. | |
| RF-16513 | Web Client | RightFax Web Delivery requires the user to manually sign in when opening a Web Delivery fax in WebClient configured for Single Sign On. | Fixed. | |
| RF-16515 | Web Client | A delegate with a delegate role of Editor is prevented from moving faxes to another folder. | Fixed. | |

| SR2 | SR2 | | | |
|----------|------------|--|------------|--|
| Issue | Component | Issue Description | Resolution | |
| RF-16162 | WorkServer | Conversions of Office 2016 documents fail. | Fixed. | |
| RF-16536 | WorkServer | When using InterConnect between RightFax servers, image files on one server are overwritten when the CurrentFile values happen to be the same. | Fixed. | |

6.7 Issues fixed in SR1

| SR1 | SR1 | | | |
|----------|-------------------|---|--|--|
| Issue | Component | Issue Description | Resolution | |
| RF-15969 | Alerting | The Alerting module crashes when multiple email addresses are used in an action that sends an alert via SMTP. | Fixed. | |
| RF-15343 | Conversion Engine | Conversion replaces letters that include diacritical marks with incorrect characters when email is submitted from Outlook via SMTP gateway. | Fixed. | |
| RF-15384 | Conversion Engine | Word not correctly applying margins when converting MHTML jobs. | Fixed. | |
| RF-15399 | Conversion Engine | Conversioncontrol.xml not allowing any of the backup MHTML converters to convert properly. | Fixed. | |
| RF-15957 | DocTransport | Call grouping can result in only one channel being used while other channels remain unused. | Adjust the milliseconds that a channel set to Both will wait for an inbound fax: | |

| SR1 | | | |
|-------|-----------|-------------------|--|
| Issue | Component | Issue Description | Resolution |
| | | | 1. Open the registry editor to HKEY_LOCAL_MACHIN E\ Software\Wow6432Node\RightFax\DocTransport\Transports\Brooktrout. 2. Create a REG_DWORD |
| | | | called WaitForRing . |
| | | | The Default value is 30000 (30 seconds). Adjust as needed. |
| | | | Specify the number of jobs a channel will check to determine if the channel can send the job. |
| | | | Open the registry editor to HKEY_LOCAL_MACHIN E\ Software\Wow6432Node\ RightFax\DocTransport. |
| | | | Create a REG_DWORD called SendAttemptsPerReceiv e . |
| | | | 3. The Default value is 1 . Adjust as needed. |
| | | | 4. The Default value is 0 . Adjust as needed. |
| | | | Save changes and exit the registry editor. |
| | | | Specify additional jobs for this DocTransport to pick up from the global queue: |
| | | | 1. Open the registry editor to HKEY_LOCAL_MACHIN E\ Software\Wow6432Node\ RightFax\DocTransport. |

| SR1 | SR1 | | | |
|----------|----------------|---|--|--|
| Issue | Component | Issue Description | Resolution | |
| | | | Create a REG_DWORD called ExtraFaxesFromSendQ ueue. | |
| RF-15984 | DocTransport | Prepended plus sign (+) stripped from dialing string of outbound calls. | Fixed. | |
| RF-15870 | Email Gateways | Warnings for missing notification data generated when No Notification is selected. | Fixed. | |
| RF-15933 | Email Gateways | Under certain conditions, the RightFax SMTP gateway strips the fax data body where the resulting fax includes only a cover sheet. | Fixed. Ensure that the conversion uses the proper converter for the gateway by doing the following: 1. Open the registry editor to: HKEY_LOCAL_MACHIN E\ Software\Wow6432Node\ RightFax\Gateway\Gateway#. 2. Create a REG_DWORD called UseTxtFileForTxtBodyT ype. 3. Set the value to 0 for SMTP gateways and to 1 for Exchange gateways. | |
| RF-15943 | Email Gateways | SMTP gateway does not clean up image files created for inbound routing from the temp.gateway folder. | Fixed. | |

| SR1 | SR1 | | | |
|----------|-----------------------------------|--|---|--|
| Issue | Component | Issue Description | Resolution | |
| RF-15979 | Email Gateways | Under certain conditions, email files with PostScript attachments fail conversion when submitted through SMTP gateway. | Fixed. To ensure conversion: 1. Open the registry editor to: HKEY_LOCAL_MACHIN E\ Software\Wow6432Node\ RightFax\Gateway\Gatew ay# 2. Create a DWORD called ForceBlankBody. 3. Set the value to 1. 4. Save changes and exit the registry editor. This registry will work in conjunction with the registry keys: ProcessNonAttachmentPart s and FilterNativelElmageAttachment | |
| RF-15841 | Exchange Web Services (EWS) | Outlook Advanced Form does not work with Secure Docs when using EWS. | Fixed. | |
| RF-14389 | External Document Connector | RightFax Ricoh MFP Connector occasionally crashing when run on Ricoh MP4002 and 5002 devices. | Fixed. | |
| RF-15375 | External Document Connector | Duplicate screen appearing when sending fax from Ricoh device. | Fixed. | |
| RF-15574 | External Document Connector | Authentication failing with SSO using badge reader. | Fixed. After applying this service release, open EDC Monitor, remove the Konica Minolta module, and then add it again. | |

| SR1 | | | | | | |
|----------|---|--|---|--|--|--|
| Issue | Component | Issue Description | Resolution | | | |
| RF-15633 | External Document Connector | Conversion to searchable PDF failing when using XML Generator. | Fixed. | | | |
| RF-15684 | External Document Connector | Xerox MFP not sending from Network ID accounts. | Fixed. After applying this service release, open EDC Monitor, remove the Xerox MFP module, and then add it again. | | | |
| RF-15296 | FaxUtil | NT linked users can view unpublished contacts. | Fixed. | | | |
| RF-15749 | FaxUtil | FaxUtil confirmation page displays incorrect page count and resulting status information for faxes with multiple retry attempts. | Fixed. | | | |
| RF-15766 | FaxUtil | Information missing from the top, bottom, and right sides of fax images when printing from FaxUtil. | Fixed. | | | |
| RF-15796 | RightFax Client Connector for Ricoh devices | Installation of the RightFax client application fails on devices that have a 7.X java card installed. | Fixed. | | | |
| RF-15908 | RightFax Client Connector for Ricoh devices | Installation of the RightFax client application fails on devices that have a Java 12.x card installed. | Fixed. | | | |

| SR1 | | | | | |
|----------|------------|--|---|--|--|
| Issue | Component | Issue Description | Resolution | | |
| RF-14624 | Server | With DNIS information now displayed in a column in FaxUtil, users can no longer configure the Server module to record the DNIS information in the billinfo1 field. | Fixed. To record DNIS information in the Billinfo1 field: 1. Open the registry editor to: HKEY_LOCAL_MACHIN E\ Software\RightFax\ FaxServer (x64:HKEY_ LOCAL_MACHINE\ Software\Wow6432Node\ RightFax\FaxServer) 2. Create a DWORD called RecordDNIS. 3. Set the value to 1. 4. Save changes and exit the registry editor. | | |
| RF-15938 | Server | Logging in to change configuration settings fails when Windows Authentication is set for SQL Connection String. | Fixed. | | |
| RF-15999 | Server | Under certain conditions, some pages of a received fax are missing the expected RTI line. | Fixed. | | |
| RF-15767 | Web Client | Refreshing Web Client multiple times causes errors on the RightFax server. | Fixed. | | |
| RF-15928 | Web Client | Web Client slow to load with high volume of traffic and a high volume of Web Clients. | Fixed. | | |

| SR1 | | | | | | |
|----------|------------|--|------------|--|--|--|
| Issue | Component | Issue Description | Resolution | | | |
| RF-15714 | Web EFM | The list of groups in Web EFM displays incorrect member count of 0 and does not include the group admin information. | Fixed. | | | |
| RF-13849 | WorkServer | Failing to convert XPS file. | Fixed. | | | |
| RF-15182 | WorkServer | Failing to convert MSG file. | Fixed. | | | |

7 Contact information

OpenText Corporation 275 Frank Tompa Drive Waterloo, Ontario Canada, N2L 0A1

OpenText My Support: https://support.opentext.com

For more information, visit www.opentext.com

Trademarks owned by Open Text. One or more patents may cover this product. For more information, please visit https://www.opentext.com/patents.

Disclaimer

No Warranties and Limitation of Liability